

STYRENE ACRYLIC CO POLYMER

STYRENE ACRYLIC COPOLYMER DISPERSIONS CAN BE USED IN A VARIETY OF INDUSTRIAL AND CONSUMER END-USE APPLICATIONS INCLUDING: ARCHITECTURAL DECORATIVE COATINGS SUCH CONSTRUCTION PRODUCTS AS CERAMIC TILE ADHESIVES, FILLERS, PUTTIES AND ELASTOMERIC ROOF COATINGS,



PRODUCT CODE	PRODUCT DESCRIPTION	VISCOSITY (cP)	SOLIDS %	pH at 25°C	SPECIFIC GRAVITY	MFFT °C	T _g °C	APPLICATIONS
LC E 1001	Styrene Acrylic	4000 - 10000	50 ± 1	8.0 - 9.5	1.03	20 - 24	24	Premium decorative interior paints
LC E 1002	Styrene Acrylic	1000 - 4000	45 ± 1	8.0 - 9.5	1.03	20 - 24	24	Premium decorative interior paints
LC E 1003	Styrene Acrylic	1200 - 5000	50 ± 1	8.0 - 9.5	1.03	16 - 20	22	Economical paint binder
LC E 1004	Styrene Acrylic	Max 1000	55 ± 1	8.0 - 9.5	1.03	0	- 4	Cement mortars, water proof membranes, etc
LC E 1005	Styrene Acrylic	3000 - 7500	50 ± 1	8.0 - 9.5	1.03	20-24	24	APEO-free high gloss performance for interior & exterior coatings
LC E 1007	Styrene Acrylic	Max 1000	55 ± 1	8.5 - 9.5	1.02	0	- 4	APEO- free construction binder
LC E 1008	Acrylic Copolymer	Max 500	36 ± 1	7.5 - 8.5	1.02	Approx 10		Binder for aqueous flexographic ink